

HCS-40



**PEDESTAL MOUNT
AVAILABLE SEPARATELY**

A REAL PRODUCT, FOR THE REAL WORLD. The HCS-40 from ClipperCreek is designed to take the wear-and-tear of everyday use in all environments. Its tough NEMA 4 outdoor rated enclosure ensures you can install this unit anywhere with confidence.

- **FAST CHARGING** - 7.7kW of power to charge your vehicle quickly
- **QUALITY** - Technology that works for the life of your current plug-in vehicle and then some
- **CONVENIENT** - 25 feet of charging cable for installation and operation flexibility
- **DURABLE** - Rugged, fully sealed NEMA 4 enclosure for installation anywhere
- **RELIABLE** - Backed by ClipperCreek's three year warranty and outstanding customer service



ClipperCreek.com

HCS-40

PRODUCT OVERVIEW

Call ClipperCreek Today!

877-694-4194

www.clippercreek.com



**HOLSTER
INCLUDED!**

ELECTRICAL SPECIFICATIONS

- **Service** - 208V to 240V - 40A, dedicated circuit
- **Charge current output power** - 208V to 240V - 32A max
- **Service ground monitor** - Constantly checks for presence of proper safety ground
- **Automatic circuit reclosure after minor power faults**
- **Charge Circuit Interruption Device** - Ground fault protection with fully automated self-test, eliminates manual user testing

MATERIAL SPECIFICATIONS

- Indoor/outdoor rated fully sealed (NEMA 4) enclosure
- Operating Temperatures: -22°F to 122°F (-30°C to 50°C)
- 19.7" L x 8.9" W x 5.3"D (500mm L x 225mm W x 135mm D)
- Installation: Hardwired or plug connected
- 25 feet charging cable - standard
- Wall mount connector holster included
- ETL Listed



AVAILABLE AS A PLUG-IN model: HCS-40P

Plugs Available: NEMA 14-50 and NEMA 6-50

CODES, STANDARDS and RECOMMENDED PRACTICES

- **UL 2594** Electric Vehicle Supply Equipment
- **UL 2231** Personal Protection Device (i.e., CCID Hardware)
- **UL 1998** Standard for Safety-Related Software
- **NEC 625** Electric Vehicle Charge System
- **SAE-J1772™** Electric Conductive Charge Coupler

